

Loader S -2219 (Standard Bucket)

A Loader Series For Agriculture &
Material Handling on Massey Tractors.



Counter Weight
on 3 Point Linkage.

Operated with Tractor Hydraulic Pump.
Tractor Reference 38 H.P - 50 H.P (2 W.D)

Description	Standard	6 - In - 1	Hi-Dump
Max. Operating Height	13'8"	14'2"	14'8"
Load Over Height	10'8"	10'8"	12'9"
Full Dump Height	9'2"	10'6"	12'6"
Bucket Rated Capacity (Struck + Heap) Volume	0.40 cu.m	0.40 cu.m	0.40 cu.m
Bucket Inside Length	1500 mm	1678 mm	1650 mm
Safe Working Load	600 kg	600 kg	600 kg

Tractor Reference : Massey 241 DI, 246 DI - Dynatrack (2 W.D)

Loader S -2224 (Standard Bucket)



Operated with Tractor Hydraulic Pump.
Tractor Reference 25 H.P – 40 H.P (2 W.D)

Description	Standard	6 - In - 1	Hi-Dump
Max. Operating Height	11'	11'4"	11'7"
Load Over Height	8'8"	8'8"	10'
Full Dump Height	7'3"	8'6"	9'7"
Bucket Rated Capacity (Struck + Heap) Volume	0.30 cu.m	0.30 cu.m	0.30 cu.m
Bucket Inside Length	1500 mm	1678 mm	1650 mm
Safe Working Load	400 kg	400 kg	400 kg

Tractor Reference : Massey 1035 DI, 7235 DI